

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Issue date: 10/16/2024 Revision date: 10/15/2025 Supersedes version of: 10/7/2025 Version: 2.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture

Trade name : DOUCE COUVERTURE UFI : 8870-J2TV-8001-43HN

Product code : BEL128

Type of product : Perfumes, fragrances
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only : Perfumes, fragrances

Use of the substance/mixture : Perfumes, frag Function or use category : Odour agents

#### 1.3. Details of the supplier of the safety data sheet

#### **BelCandle**

Rue de la Jonction,53 6880 BERTRIX BELGIQUE

Tél.: 0032 491 74 59 81

contact@belcandle.be www.belcandle.be

### 1.4. Emergency telephone number

Emergency number : Belgique : +32 070 245 245 ; France : +33 (0)1 45 42 59

59 ; Luxembourg : +32 (0) 70 245 245

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

#### 2.2. Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS09

Signal word (CLP) : Warning

Contains : 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone; Amyl cinnamic

aldehyde; Aldehyde C-16; COUMARIN; Orange oil ; Majantol; Hydroxy; Benzyl alcohol;

Lemon oil; Citronellol Pure; CUPRESSUS FUNEBRIS WOOD OIL; Linalool

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

10/15/2025 (Revision date) ' EN (English) 1/35

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Precautionary statements (CLP)

: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989- 04	3 – 6	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Amyl cinnamic aldehyde	CAS-No.: 122-40-7 EC-No.: 204-541-5	2.3 – 4.5	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
ACETYL HEXAMETHYL TETRALIN	CAS-No.: 21145-77-7 EC-No.: 244-240-6	1.3 – 2.5	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB)	CAS-No.: 1222-05-5 EC-No.: 214-946-9 EC Index-No.: 603-212-00-7 REACH-no: 01-2119488227- 29	1.3 – 2.5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	1 – 2	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040- 60	0.9500095 – 1.980012375	Eye Irrit. 2, H319
tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans)	CAS-No.: 63500-71-0 EC-No.: 405-040-6 EC Index-No.: 603-101-00-3 REACH-no: 01-000015458-64	0.45 – 1.8	Eye Irrit. 2, H319
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	0.7 – 1.35	Acute Tox. 4 (Oral), H302
Sandal Mysore Core	CAS-No.: 28219-60-5 EC-No.: 248-907-2	0.7 – 1.35	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

# Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.): 2,2-dimethyl-3-(3-methylphenyl)propanol	CAS-No.: 103694-68-4 EC-No.: 403-140-4 EC Index-No.: 603-138-00-5	0.006 – 1.25	Skin Sens. 1, H317 Aquatic Chronic 3, H412
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353- 35	0.5 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Carbitol substance with national workplace exposure limit(s) (AT, DE, EE, SE, SI, CH)	CAS-No.: 111-90-0 EC-No.: 203-919-7 REACH-no: 01-2119475105- 42	0.43398 – 0.904125	Not classified
Aldehyde C-16	CAS-No.: 77-83-8 EC-No.: 201-061-8 REACH-no: 01-2119967770- 28	0.4 – 0.75	Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Citronellol Pure	CAS-No.: 106-22-9 EC-No.: 203-375-0 REACH-no: 01-2119453995- 23	0.300005 – 0.50000625	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Hydroxy	CAS-No.: 107-75-5 EC-No.: 203-518-7 REACH-no: 01-2119973482- 31	0.24644 – 0.44675	Eye Irrit. 2, H319 Skin Sens. 1B, H317
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	0.2 – 0.35	Aquatic Chronic 3, H412
Benzaldehyde substance with national workplace exposure limit(s) (BG, FI, HU, LT, LV, PL)	CAS-No.: 100-52-7 EC-No.: 202-860-4 EC Index-No.: 605-012-00-5 REACH-no: 01-2119455540-	0.2 – 0.3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361 STOT SE 3, H335
CUPRESSUS FUNEBRIS WOOD OIL	CAS-No.: 85085-29-6 EC-No.: 285-360-9	0.2 – 0.3	Skin Corr. 1, H314 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-	0.1 – 0.25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Citrus medica limonum (Lemon) peel oil	CAS-No.: 8008-56-8 EC-No.: 284-515-8	0.1 – 0.25	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016- 42	0.1 – 0.2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.000254 – 0.0003175	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.00000375	Not classified

Full text of H- and EUH-statements: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow affected person to

breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.

Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated

clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison

center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep

container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

Germany

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

10/15/2025 (Revision date) EN (English) 6/35

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Joint storage table .GK 1 LGK 2A LGK 2B LGK 3 LGK 4.1A LGK 4.2 LGK 4.1B LGK 4.3 LGK 5.1A LGK 5.1B LGK 5.1C LGK 5.2 LGK 6.1A LGK 6.1B LGK 6.1C LGK 6.1D LGK 6.2 LGK 7 LGK 8A LGK 8B

Joint storage not permitted for : LGK 1, LGK 2A, LGK 5.1A, LGK 6.2, LGK 7

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.2, LGK 5.1B, LGK 5.1C, LGK 5.2

LGK 10

Joint storage permitted for : LGK 2B, LGK 3, LGK 4.1B, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B,

LGK 11

LGK 10, LGK 11, LGK 12, LGK 13, LGK 10-13

LGK 12

**LGK 13** 

LGK 10-13

**Switzerland** 

Storage class (LK) : LK 10/12 - Liquids

### 7.3. Specific end use(s)

No additional information available

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

National occupational exposure and biological limit values

Carbitol (111-90-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	35 mg/m³	
	6 ppm	
MAK (OEL STEL)	140 mg/m³	
	24 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	50.1 mg/m³	
	10 ppm	
OEL chemical category	Skin notation	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA)	35 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	6 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Slovenia - Occupational Exposure Limits		
OEL TWA	35 mg/m³	
	6 ppm	
OEL STEL	70 mg/m³	
	12 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	80 mg/m³	
	15 ppm	
KGV (OEL STEL)	170 mg/m³	
	30 ppm	

# Safety Data Sheet

Carbitol (111-90-0)		
OEL chemical category	Skin notation	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	50 mg/m³ (aerosol, inhalable dust, vapour)	
KZGW (OEL STEL)	100 mg/m³ (aerosol, inhalable dust, vapour)	
Benzaldehyde (100-52-7)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	4.4 mg/m³	
	1 ppm	
HTP (OEL C)	17.4 mg/m³	
	4 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³	
CK (OEL STEL)	10 mg/m³	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	10 mg/m³	
NDSCh (OEL STEL)	40 mg/m³	
Benzyl acetate (140-11-4)		
Belgium - Occupational Exposure Limits		
OEL TWA	62 mg/m³	
	10 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA	61 mg/m³	
	10 ppm	
OEL STEL	122 mg/m³	
	20 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA	10 ppm	
OEL STEL	30 ppm (calculated)	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	

# Safety Data Sheet

Benzyl acetate (140-11-4)		
Portugal - Occupational Exposure Limits		
OEL TWA	10 ppm	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	
Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
	8 ppm	
OEL STEL	80 mg/m³	
	13 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	62 mg/m³	
	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH® TLV® TWA	10 ppm	
ACGIH® chemical category	Not Classifiable as a Human Carcinogen	
benzyl alcohol (100-51-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	40 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	45 mg/m³	
	10 ppm	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA)	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
OEL chemical category	Skin notation	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	22 mg/m³	
	5 ppm	
OEL STEL	44 mg/m³	

# Safety Data Sheet

benzyl alcohol (100-51-6)		
	10 ppm	
OEL chemical category	Potential for cutaneous absorption	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	22 mg/m³ (aerosol, vapour)	
	5 ppm (aerosol, vapour)	
OEL chemical category	Skin notation	
Toluene (108-88-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	192 mg/m³	
	50 ppm	
IOEL STEL	384 mg/m³	
	100 ppm	
Remark	Possibility of significant uptake through the skin	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	190 mg/m³	
	50 ppm	
MAK (OEL STEL)	380 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	
Belgium - Occupational Exposure Limits		
OEL TWA	77 mg/m³	
	20 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
OEL chemical category	Skin, Skin notation	
Bulgaria - Occupational Exposure Limits		
OEL TWA	192 mg/m³	
	50 ppm	
OEL STEL	384 mg/m³	
	100 ppm	
Bulgaria - Biological limit values		
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA)	192 mg/m³	
	50 ppm	
KGVI (OEL STEL)	384 mg/m³	
	100 ppm	
OEL chemical category	Skin notation	

# Safety Data Sheet

Toluene (108-88-3)	
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)  1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m³
OEL chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis)  1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)  1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis)  1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m³
	25 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m³

# Safety Data Sheet

Toluene (108-88-3)	
	25 ppm
HTP (OEL STEL)	380 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	·
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m³ (restrictive limit)
	20 ppm (restrictive limit)
VLE (OEL C/STEL)	384 mg/m³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption
France - Biological limit values	
BLV	20 μg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi- quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority,
	the values for this substance must be decided and/or determined on a case by case basis.  Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 90	0)
AGW (OEL TWA)	190 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903)	
Biological limit value	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 μg/l Parameter: Toluene - Medium: urine - Sampling time: end of exposure or shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: at the end of the shift, in case of long-term exposure after several previous shifts
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	•
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
	I .

# Safety Data Sheet

Hungary - Occupational Exposure Limits  AK (OEL TWA)	
AK (OEL TWA)	
	190 mg/m³
CK (OEL STEL)	384 mg/m³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m³
	14 ppm
OEL chemical category	skin - potential for cutaneous exposure
Latvia - Biological Exposure Indices	
BEI	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of exposure (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: at the end of exposure or shift (after hydrolysis)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m³
	50 ppm
TPRV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Reproductive toxin, Skin notation
Luxembourg - Occupational Exposure Limits	1
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	1
OEL TWA	192 mg/m³
	50 ppm

# Safety Data Sheet

Toluene (108-88-3)	
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m³
NDSCh (OEL STEL)	200 mg/m³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	384 mg/m³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m³
	50 ppm
NPHV (OEL C)	384 mg/m³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 μg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift

# Safety Data Sheet

Toluene (108-88-3)	
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m³
	50 ppm
OEL STEL	384 mg/m³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift     0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek     0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m³
	50 ppm
KGV (OEL STEL)	384 mg/m³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m³
	50 ppm
KZGW (OEL STEL)	760 mg/m³
	200 ppm

# Safety Data Sheet

Toluene (108-88-3)			
OEL chemical category	Skin notation, Category 2 reproductive toxin		
Switzerland - BAT	•		
BAT	600 μg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 μmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 μmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 μg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift		
USA - ACGIH - Occupational Exposure Limits			
ACGIH® TLV® TWA	20 ppm		
ACGIH® chemical category	Not Classifiable as a Human Carcinogen		
USA - ACGIH - Biological Exposure Indices			
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)		
Dipropylene glycol monomethyl ether (345	90-94-8)		
EU - Indicative Occupational Exposure Limit (IO	EL)		
IOEL TWA	308 mg/m³		
	50 ppm		
Remark	Possibility of significant uptake through the skin		
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	307 mg/m³ (mixed isomers)		
	50 ppm (mixed isomers)		
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)		
	100 ppm (isomers mixtures)		
OEL chemical category	Skin notation		
Belgium - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Skin, Skin notation		
Bulgaria - Occupational Exposure Limits	Bulgaria - Occupational Exposure Limits		
OEL TWA	308 mg/m³		
	50 ppm		
Croatia - Occupational Exposure Limits			
GVI (OEL TWA)	308 mg/m³		
	50 ppm		
OEL chemical category	Skin notation		

# Safety Data Sheet

Dipropylene glycol monomethyl ether (3459	90-94-8)	
Cyprus - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin-potential for cutaneous absorption	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	270 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Denmark - Occupational Exposure Limits		
OEL TWA	309 mg/m³	
	50 ppm	
OEL STEL	618 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	310 mg/m³	
	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
France - Occupational Exposure Limits		
VME (OEL TWA)	308 mg/m³ (restrictive limit)	
	50 ppm (restrictive limit)	
OEL chemical category	Risk of cutaneous absorption	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA)	310 mg/m³ (isomer mixture)	
	50 ppm (isomer mixture)	
Gibraltar - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Greece - Occupational Exposure Limits		
OEL TWA	600 mg/m³	
	100 ppm	
OEL STEL	900 mg/m³	
	150 ppm	
OEL chemical category	skin - potential for cutaneous absorption	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)	
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m³
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-1-ol)
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m³ (indicative limit value)

# Safety Data Sheet

OEL STEL     50 ppm (inclicative limit value)       OEL Chemical category     150 ppm       OEL TWA     308 mg/m²       OEL Chemical category     50 ppm       OEL Chemical category     308 mg/m²       50 ppm     50 ppm       OEL Chemical category     70 ppm       OEL TWA     308 mg/m²       50 ppm     50 ppm       OEL TWA     308 mg/m²       50 ppm     50 ppm       OEL TWA     308 mg/m²       50 ppm     50 ppm       OEL TWA     50 ppm       OEL Chemical category     50 ppm       OEL Chemical category     50 ppm       OEL Chemical category     90 mg/m²       Spain - Occupational Exposure Limits     50 ppm (inclicative limit value)       OEL Chemical category     300 mg/m² (inclicative limit value)       OEL Chemical category     300 mg/m²       Several - Occupational Exposure Limits     50 ppm (inclicative limit value)       OEL Chemical category     300 mg/m²       OEL Chemical category     300 mg/m²       OEL Chemical category     301 mg/m²       OEL Chemical category     301 mg/m²       OEL Chemical category     302	Dipropylene glycol monomethyl ether (34590-94-8)		
OEL chemical category         skin - potential for cutaneous exposure indicative limit value           Romania - Occupational Exposure Limits           OEL 1 TWA         308 mg/m²           OEL chemical category         \$kin nodation           Siovakia - Occupational Exposure Limits           NPHY (OEL TWA)         208 mg/m²           60 pm         Potential for cutaneous absorption           Siovania - Occupational Exposure Limits           OEL TWA         308 mg/m²           50 ppm         50 ppm           OEL STEL         308 mg/m²           60 ppm         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)           50 ppm         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)           50 ppm (indicative limit value)           50 ppm (indicative		50 ppm (indicative limit value)	
Romania - Occupational Exposure Limits         308 mg/m²           OEL TWA         308 mg/m²           50 ppm         50 ppm           OEL chemical category         \$10 molation           Slovakia - Occupational Exposure Limits         To ppm           OEL themical category         Potential for cutaneous absorption           Slovenia - Occupational Exposure Limits         50 ppm           OEL TWA         308 mg/m²           50 ppm         50 ppm           OEL Chemical category         Potential for cutaneous absorption           OEL Chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         To ppm (indicative limit value)           OEL chemical category         \$8 mg/m² (indicative limit value)           OEL chemical category	OEL STEL	150 ppm	
QEL TWA         308 mg/m²           QEL chemical category         \$in notation           Slovakia - Occupational Exposure Limits         308 mg/m²           PHY (QEL TWA)         308 mg/m²           GEL chemical category         Potential for cutaneous absorption           Slovenia - Occupational Exposure Limits           QEL TWA         308 mg/m²           50 ppm         50 ppm           QEL STEL         308 mg/m²           50 ppm         60 ppm           QEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         50 ppm           VLA-ED (QEL TWA)         308 mg/m² (indicative limit value)           QEL chemical category         \$60 ppm (indicative limit value)           Sweden - Occupational Exposure Limits           NGY (QEL TWA)         50 ppm (indicative limit value)           So ppm         50 ppm (indicative limit value)           SWeden - Occupational Exposure Limits         For ppm (indicative limit value)           SWeden - Occupational Exposure Limits         For ppm           KGY (QEL TWA)         450 mg/m²           Sp ppm         For ppm           QEL chemical category         50 ppm           WEL TYAL (QEL TWA)         50	OEL chemical category	skin - potential for cutaneous exposure indicative limit value	
Description         50 ppm           OEL chemical category         5kin notation           Stowakia - Occupational Exposure Limits         50 ppm           OEL chemical category         Potential for cutaneous absorption           Stownia - Occupational Exposure Limits         50 ppm           OEL TWA         308 mg/m²           50 ppm         50 ppm           OEL STEL         308 mg/m²           50 ppm         60 ppm           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         70 ppm (indicative limit value)           Spain - Occupational Exposure Limits         50 ppm (indicative limit value)           OEL chemical category         308 mg/m² (indicative limit value)           OEL chemical category         300 mg/m² (indicative limit value)           OEL Chemical category         300 mg/m² (indicative limit value)           OEL Chemical category         300 mg/m² (indicative limit value)           So ppm           KEY (OEL TWA)         300 mg/m² (indicative limit value)           OEL chemical category         300 mg/m² (indicative limit value)           OEL chemical category         300 mg/m² (indicative limit value)           OEL Chemical categor	Romania - Occupational Exposure Limits		
Solurabia - Occupational Exposure Limits         Nethology         308 mg/m³           DEL chemical category         Potential for cutaneous absorption           Slovenia - Occupational Exposure Limits         Potential for cutaneous absorption           Slovenia - Occupational Exposure Limits         308 mg/m³           OEL TWA         308 mg/m³           50 ppm         50 ppm           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         VLA-ED (OEL TWA)           Spain - Occupational Exposure Limits         VLA-ED (OEL TWA)           Submissional Exposure Limits         Submissional Exposure Limits           VVA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           OEL chemical category         sin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits         Submissional Exposure Limits           WEV (OEL TWA)         300 mg/m³           50 ppm         Spain - Qualificative limit value           VOEL chemical category         \$00 mg/m³           Sp ppm         \$00 mg/m³           VILLE STELL         \$00 mg/m³           Sp ppm         \$00 mg/m³           VEL TWA (OEL TWA)         \$00 mg/m³           Sp ppm (calculated)         \$00 mg/m³	OEL TWA	308 mg/m³	
Slovakia - Occupational Exposure Limits           NPHV (OEL TWA)         308 mg/m³           50 ppm         OEL chemical category           Potential for cutaneous absorption           Slovenia - Occupational Exposure Limits           OEL TWA         308 mg/m³           50 ppm           OEL STEL         308 mg/m³           50 ppm           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           50 ppm (indicative limit value)         50 ppm (indicative limit value)           Sweden - Occupational Exposure Limits           Novel (OEL TWA)         300 mg/m³           50 ppm         450 mg/m³           50 ppm         450 mg/m³           50 ppm         50 ppm           Vulted Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA)         308 mg/m³           50 ppm         50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           Value Calculated)           WEL OFLE STEL (OEL STEL)         924 mg/m³ (calculated)           Value Calculated) <td></td> <td>50 ppm</td>		50 ppm	
NPHV (DEL TWA)         308 mg/m²           50 ppm           OEL chemical category         Potential for cutaneous absorption           Stovenia - Occupational Exposure Limits         308 mg/m²           DEL TWA         308 mg/m²           50 ppm         50 ppm           OEL STEL         308 mg/m²           50 ppm         Formal           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)         308 mg/m² (indicative limit value)           509 pm           KGV (OEL TWA)         300 mg/m²           509 pm           KGV (OEL STEL)         450 mg/m²           509 pm           Value STEL (OEL STEL)         308 mg/m²         50 ppm           WEL TWA (OEL TWA)         308 mg/m²         50 ppm           509 pm	OEL chemical category	Skin notation	
Description         50 ppm           OEL chemical category         Potential for cutaneous absorption           Stovenia - Occupational Exposure Limits           DEL TWA         308 mg/m²           60 ppm         50 ppm           OEL STEL         70 ppm           0EL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         VLA-ED (OEL TWA)         308 mg/m² (indicative limit value)           0EL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits         50 ppm (indicative limit value)           0EL chemical category         skin - potential for cutaneous absorption           XPY (OEL TWA)         300 mg/m²           60 ppm         50 ppm           KEY (OEL STEL)         50 ppm           0EL chemical category         50 mg/m²           VEL twingdom - Occupational Exposure Limits         50 ppm           WEL TWA (OEL TWA)         308 mg/m²           50 ppm         50 ppm           WEL chemical category         50 ppm (calculated)           WEL chemical category         50 ppm (calculated)           WEL chemical category         50 ppm (calculated)           Norway - Occupational Exposure	Slovakia - Occupational Exposure Limits		
OEL chemical category         Potential for cutaneous absorption           Siovenia - Occupational Exposure Limits           OEL TWA         308 mg/m³           50 ppm         50 ppm           OEL STEL         308 mg/m³           50 ppm         50 ppm           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           50 ppm (indicative limit value)           60 EL chemical category         skin potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NY         50 ppm           KGY (OEL TWA)         300 mg/m³           50 ppm           KGY (OEL STEL)         450 mg/m³           60 ppm           VILITIES (Mindom - Occupational Exposure Limits           WEL TWA (OEL TWA)         308 mg/m³           50 ppm           WEL STEL (OEL STEL)         294 mg/m² (calculated)           150 ppm (calculated)         150 ppm (calculated)           Norway - Occupational Exposure Limits         150 ppm (calculated)           Norway - Occupational Exposure Limits         50 ppm           Kortidisverdi (OEL TWA)         300 mg/m² </td <td>NPHV (OEL TWA)</td> <td>308 mg/m³</td>	NPHV (OEL TWA)	308 mg/m³	
Slovenia - Occupational Exposure Limits           OEL TWA         308 mg/m³           60 ppm         50 ppm           OEL STEL         308 mg/m³           50 ppm         50 ppm           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         308 mg/m³ (indicative limit value)           CPL chemical category         308 mg/m³ (indicative limit value)           Swedon - Occupational Exposure Limits           KGY (OEL TWA)         300 mg/m³           50 ppm           KGY (OEL STEL)         450 mg/m³           50 ppm           KGY (OEL TWA)         308 mg/m³           50 ppm           VILITED (SETEL)         450 mg/m³           50 ppm           VILITED (SETEL)         308 mg/m³           50 ppm           WEL STEL (OEL STEL)         308 mg/m³           50 ppm           WEL chemical category         308 mg/m³           50 ppm           WEL chemical category         70 ppm (calculated)           WEL chemical category         70 ppm (calculated)           WEL chemical category         70 ppm (calculated) <tr< td=""><td></td><td>50 ppm</td></tr<>		50 ppm	
OEL TWA         308 mg/m²           50 ppm         308 mg/m²           50 ppm         50 ppm           OEL Chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits         308 mg/m² (indicative limit value)           VLA-ED (OEL TWA)         308 mg/m² (indicative limit value)           OEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits         win - potential for cutaneous absorption           KSY (OEL TWA)         300 mg/m²           50 ppm         450 mg/m²           75 ppm         75 ppm           OEL chemical category         8 kn notation           WEL TWA (OEL TWA)         308 mg/m²           50 ppm         50 ppm           WEL TWA (OEL TWA)         924 mg/m² (calculated)           50 ppm         924 mg/m² (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits         924 mg/m² (calculated)           For ppm (calculated)         50 ppm           Norway - Occupational Exposure Limits         90 mg/m²           So ppm         50 ppm           Kortiddsverd (OEL TWA)         30	OEL chemical category	Potential for cutaneous absorption	
For prm           OEL STEL         308 mg/m³           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           50 ppm (indicative limit value)         50 ppm (indicative limit value)           Sweden - Occupational Exposure Limits           NGY (OEL TWA)         300 mg/m³           50 ppm         450 mg/m³           50 ppm         75 ppm           OEL chemical category         450 mg/m³           Mg/m³ (calculated)           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA)         308 mg/m³           50 ppm         50 ppm           WEL CHEL (OEL STEL)         924 mg/m² (calculated)           150 ppm (calculated)         150 ppm (calculated)           Norway - Occupational Exposure Limits           Spen (calculated)           Norway - Occupational Exposure Limits           Spen (calculated)           50 ppm           Kortidsverdi (OEL TWA)         300 mg/m³           50 ppm           Spen (calculated)           50 ppm	Slovenia - Occupational Exposure Limits		
DEL STEL     308 mg/m³       OEL Chemical category     potential for cutaneous absorption       Spain-Occupational Exposure Limits       VLA-ED (OEL TWA)     308 mg/m³ (indicative limit value)       OEL chemical category     skin - potential for cutaneous absorption       Sweden - Occupational Exposure Limits       NEY (OEL TWA)     300 mg/m³       50 ppm       KEY (OEL STEL)     450 mg/m³       0EL chemical category     Skin notation       United Kingdom - Occupational Exposure Limits       WEL TWA (OEL TWA)     308 mg/m³       50 ppm       WEL STEL (OEL STEL)     924 mg/m² (calculated)       WEL STEL (OEL STEL)     924 mg/m² (calculated)       WEL chemical category     Potential for cutaneous absorption       Norway - Occupational Exposure Limits     50 ppm (calculated)       Norway - Occupational Exposure Limits     50 ppm (calculated)       Renseverdi (OEL TWA)     300 mg/m³       50 ppm       Korticitsverdi (OEL STEL)     37 mg/m² (value calculated)       50 ppm       Korticitsverdi (OEL STEL)     37 mg/m² (value calculated)       50 ppm (value calculated)     50 ppm (value calculated)	OEL TWA	308 mg/m³	
So pm           OEL chemical category         Potential for cutaneous absorption           Spain - Occupational Exposure Limits           VLA-ED (OEL TWA)         308 mg/m² (indicative limit value)           50 ppm (indicative limit value)         50 ppm (indicative limit value)           Sweden - Occupational Exposure Limits           NBY (OEL TWA)         300 mg/m²           50 ppm         50 ppm           KSY (OEL STEL)         450 mg/m²           To ppm           OEL chemical category         8kin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA)         308 mg/m²           50 ppm         50 ppm           WEL STEL (OEL STEL)         924 mg/m² (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits           So ppm           Norway - Occupat		50 ppm	
OEL chemical category       Potential for cutaneous absorption         Spain - Occupational Exposure Limits         VLA-ED (OEL TWA)       308 mg/m³ (indicative limit value)         50 ppm (indicative limit value)       60 ppm (indicative limit value)         Sweden - Occupational Exposure Limits         Ng/ (OEL TWA)       300 mg/m³         50 ppm       50 ppm         KGV (OEL STEL)       450 mg/m³         To ppm         OEL chemical category       308 mg/m³         United Kingdom - Occupational Exposure Limits         WEL TWA (OEL TWA)       308 mg/m³         50 ppm       50 ppm (calculated)         WEL STEL (OEL STEL)       924 mg/m³ (calculated)         WEL chemical category       Potential for cutaneous absorption         Norway - Occupational Exposure Limits         Genseverdi (OEL TWA)       300 mg/m³         50 ppm         Kortidsverdi (OEL STEL)       375 mg/m³ (value calculated)         75 ppm (value calculated)         75 ppm (value calculated)	OEL STEL	308 mg/m³	
Spain - Occupational Exposure Limits         VLA-ED (OEL TWA)       308 mg/m³ (indicative limit value)         50 ppm (indicative limit value)       50 ppm (indicative limit value)         OEL chemical category       skin - potential for cutaneous absorption         Sweden - Occupational Exposure Limits         KGY (OEL TWA)         300 mg/m³         50 ppm         OEL chemical category         Winted Kingdom - Occupational Exposure Limits         WEL TWA (OEL TWA)         308 mg/m³         50 ppm         WEL STEL (OEL STEL)         WEL chemical category       924 mg/m³ (calculated)         WEL chemical category       Potential for cutaneous absorption         Norway - Occupational Exposure Limits         So ppm         Norway - Occupational Exposure Limits         So ppm         Kortidsverdi (OEL TWA)         300 mg/m³       50 ppm         Kortidsverdi (OEL STEL)         375 mg/m³ (value calculated)       75 ppm (value calculated)         75 ppm (value calculated)		50 ppm	
VLA-ED (OEL TWA)         308 mg/m³ (indicative limit value)           OEL chemical category         skin - potential for cutaneous absorption           Sweden - Occupational Exposure Limits           NGY (OEL TWA)         300 mg/m³           60 ppm         450 mg/m³           75 ppm         75 ppm           OEL chemical category         50kin notation           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA)         308 mg/m³           50 ppm           WEL STEL (OEL STEL)         224 mg/m³ (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits         To ppm (calculated)           Norway - Occupational Exposure Limits         50 ppm           Kortitidsverdi (OEL TWA)         300 mg/m³           50 ppm           Kortitidsverdi (OEL STEL)         375 mg/m² (value calculated)           75 ppm (value calculated)	OEL chemical category	Potential for cutaneous absorption	
DEL chemical category     skin - potential for cutaneous absorption       Sweden - Occupational Exposure Limits     300 mg/m³       KGV (OEL TWA)     300 mg/m³       50 ppm       KGV (OEL STEL)     450 mg/m³       OEL chemical category     3kin notation       United Kingdom - Occupational Exposure Limits       WEL TWA (OEL TWA)     308 mg/m³       50 ppm       WEL STEL (OEL STEL)     924 mg/m³ (calculated)       150 ppm (calculated)       WEL chemical category     Potential for cutaneous absorption       Norway - Occupational Exposure Limits       Torquare (OEL TWA)     300 mg/m³       50 ppm       Korttidsverdi (OEL STEL)     375 mg/m³ (value calculated)       75 ppm (value calculated)       75 ppm (value calculated)       75 ppm (value calculated)       75 ppm (value calculated)	Spain - Occupational Exposure Limits		
CPEL chemical category       skin - potential for cutaneous absorption         Sweden - Occupational Exposure Limits         NGV (OEL TWA)       300 mg/m³         50 ppm       450 mg/m³         KGV (OEL STEL)       450 mg/m³         OEL chemical category       5kin notation         United Kingdom - Occupational Exposure Limits         WEL TWA (OEL TWA)       308 mg/m³         50 ppm       924 mg/m³ (calculated)         150 ppm (calculated)       150 ppm (calculated)         WEL chemical category       Potential for cutaneous absorption         Norway - Occupational Exposure Limits         Crenseverdi (OEL TWA)       300 mg/m³         50 ppm       50 ppm         Korttidsverdi (OEL STEL)       375 mg/m³ (value calculated)         75 ppm (value calculated)	VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)	
Sweden - Occupational Exposure Limits         NGV (OEL TWA)       300 mg/m³         50 ppm       50 ppm         KGV (OEL STEL)       450 mg/m³         75 ppm       75 ppm         OEL chemical category       Skin notation         United Kingdom - Occupational Exposure Limits         WEL TWA (OEL TWA)       308 mg/m³         50 ppm       50 ppm         WEL STEL (OEL STEL)       924 mg/m³ (calculated)         150 ppm (calculated)       150 ppm (calculated)         Norway - Occupational Exposure Limits         Norway - Occupational Exposure Limits         Step pm (value calculated)         Korttidsverdi (OEL TWA)       300 mg/m³         50 ppm       50 ppm         Korttidsverdi (OEL STEL)       375 mg/m³ (value calculated)         75 ppm (value calculated)       75 ppm (value calculated)		50 ppm (indicative limit value)	
NGV (OEL TWA)         300 mg/m³           KGV (OEL STEL)         450 mg/m³           T5 ppm         75 ppm           United Kingdom - Occupational Exposure Limits         Skin notation           WEL TWA (OEL TWA)         308 mg/m³           50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           WEL chemical category         Potential for cutaneous absorption           Norway - Occupational Exposure Limits           Grenseverdi (OEL TWA)         300 mg/m³           50 ppm           Korttidsverdi (OEL STEL)         375 mg/m³ (value calculated)           T5 ppm (value calculated)           75 ppm (value calculated)	OEL chemical category	skin - potential for cutaneous absorption	
KGV (OEL STEL)         450 mg/m³           CDEL chemical category         50 ppm           OEL chemical category         50 mg/m³           Well TWA (OEL TWA)         308 mg/m³           50 ppm           WEL STEL (OEL STEL)         924 mg/m³ (calculated)           150 ppm (calculated)           Norway - Occupational Exposure Limits           Grenseverdi (OEL TWA)         300 mg/m³           50 ppm           Korttidsverdi (OEL STEL)         375 mg/m³ (value calculated)           75 ppm (value calculated)           75 ppm (value calculated)	Sweden - Occupational Exposure Limits		
KGV (OEL STEL)450 mg/m³75 ppmOEL chemical categorySkin notationUnited Kingdom - Occupational Exposure LimitsWEL TWA (OEL TWA)308 mg/m³50 ppmWEL STEL (OEL STEL)924 mg/m³ (calculated)WEL chemical categoryPotential for cutaneous absorptionNorway - Occupational Exposure LimitsGrenseverdi (OEL TWA)300 mg/m³50 ppmKorttidsverdi (OEL STEL)375 mg/m³ (value calculated)Korttidsverdi (OEL STEL)375 mg/m³ (value calculated)75 ppm (value calculated)	NGV (OEL TWA)	300 mg/m³	
DEL chemical category Skin notation  United Kingdom - Occupational Exposure Limits  WEL TWA (OEL TWA) 308 mg/m³ 50 ppm  WEL STEL (OEL STEL) 924 mg/m³ (calculated) 150 ppm (calculated) WEL chemical category Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) 300 mg/m³ 50 ppm  Korttidsverdi (OEL STEL) 375 mg/m³ (value calculated) 75 ppm (value calculated)		50 ppm	
OEL chemical category  Wited Kingdom - Occupational Exposure Limits  WEL TWA (OEL TWA)  308 mg/m³ 50 ppm  WEL STEL (OEL STEL)  924 mg/m³ (calculated) 150 ppm (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  50 ppm  300 mg/m³ 50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated) 75 ppm (value calculated)	KGV (OEL STEL)	450 mg/m³	
WEL TWA (OEL TWA)  WEL STEL (OEL STEL)  WEL chemical category  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  Xortidsverdi (OEL STEL)  308 mg/m³ 50 ppm  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³ 50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)		75 ppm	
WEL TWA (OEL TWA)  308 mg/m³ 50 ppm  WEL STEL (OEL STEL)  924 mg/m³ (calculated) 150 ppm (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³ 50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated) 75 ppm (value calculated)	OEL chemical category	Skin notation	
WEL STEL (OEL STEL)  924 mg/m³ (calculated)  150 ppm (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)	United Kingdom - Occupational Exposure Limits		
WEL STEL (OEL STEL)  924 mg/m³ (calculated)  150 ppm (calculated)  WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)	WEL TWA (OEL TWA)	308 mg/m³	
MEL chemical category Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)		50 ppm	
WEL chemical category  Potential for cutaneous absorption  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)	WEL STEL (OEL STEL)	924 mg/m³ (calculated)	
Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA)  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated) 75 ppm (value calculated)		150 ppm (calculated)	
Grenseverdi (OEL TWA)  300 mg/m³  50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)	WEL chemical category	Potential for cutaneous absorption	
50 ppm  Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)	Norway - Occupational Exposure Limits		
Korttidsverdi (OEL STEL)  375 mg/m³ (value calculated)  75 ppm (value calculated)	Grenseverdi (OEL TWA)	300 mg/m³	
75 ppm (value calculated)		50 ppm	
	Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)	
OEL chemical category Skin notation		75 ppm (value calculated)	
	OEL chemical category	Skin notation	

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	50 ppm (Dipropylene glycol methyl ether)

## 8.2. Exposure controls

#### **Appropriate engineering controls**

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Personal protective equipment symbol(s):





#### Eye and face protection

### Eye protection:

Chemical goggles or safety glasses. Safety glasses

#### **Skin protection**

## Skin and body protection:

Wear suitable protective clothing

### Hand protection:

Wear protective gloves.

#### **Respiratory protection**

### Respiratory protection:

Wear appropriate mask

#### **Environmental exposure controls**

#### **Environmental exposure controls:**

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke during use.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Conforms to standard.

Odour: characteristic.Odour threshold: Not availableMelting point: Not applicableFreezing point: Not availableBoiling point: Not available

Flammability : Non flammable, Not applicable

Lower explosion limit : Not available

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

: Not available Upper explosion limit Flash point > 93 °C Auto-ignition temperature Not available Decomposition temperature Not available : Not available рΗ : Not available Viscosity, kinematic : Not available Solubility Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : 0.000498109 mm Hg (calculated value)

Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

#### 9.2. Other information

#### Other safety characteristics

VOC content : 5.04950875 % (calculated value)(CARB VOC) (%w/w)

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Not established.

# 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

# 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Amyl cinnamic aldehyde (122-40-7)		
LD50 oral rat	3730 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 2000 mg/kg (Source: CHEMVIEW)	
ACETYL HEXAMETHYL TETRALIN (21145-77-7)		
LD50 oral rat	570 mg/kg (Source: NLM_CIP)	
LD50 oral	1000 mg/kg	
LD50 dermal rabbit	> 5 g/kg (Source: NLM_HSDB)	

# Safety Data Sheet

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylind	1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)	
LD50 oral rat	> 3250 mg/kg (Source: CHEMVIEW)	
LD50 dermal rabbit	> 3250 mg/kg (Source: CHEMVIEW)	
LC50 Inhalation - Rat	> 5.04 mg/l/4h	
Vanillin (121-33-5)		
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)	
LD50 dermal	2600 mg/kg	
Ethyl maltol (4940-11-8)		
LD50 oral rat	1150 mg/kg (Source: NLM_CIP)	
LD50 oral	1200 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)	
Aldehyde C-16 (77-83-8)		
LD50 oral rat	5470 mg/kg (Source: NLM_CIP)	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)	
COUMARIN (91-64-5)		
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rat	293 mg/kg (Source: ECHA_API)	
Orange oil (8008-57-9)		
LD50 oral rat	4400 mg/kg (Source: NZ_CCID)	
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)	
3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.)	: 2,2-dimethyl-3-(3-methylphenyl)propanol (103694-68-4)	
LD50 oral	3440 mg/kg	
LD50 dermal rabbit	> 5 ml/kg (Source: ECHA_API)	
Carbitol (111-90-0)		
LD50 oral rat	10502 mg/kg (Source: OECD_SIDS)	
LD50 dermal rabbit	9143 mg/kg (Source: OECD_SIDS)	
LC50 Inhalation - Rat	> 5240 mg/m³ (Exposure time: 4 h Source: NLM_CIP)	
Hydroxy (107-75-5)		
LD50 oral rat	> 6400 mg/kg (Source: ECHA)	
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)	
tetrahydro-2-isobutyl-4-methylpyran-4-ol, mixed isomers (cis and trans) (63500-71-0)		
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)	
Benzaldehyde (100-52-7)		
LD50 oral rat	1292 mg/kg (Source: JAPAN_GHS)	
LD50 dermal rabbit	> 1250 mg/kg (Source: JAPAN_GHS)	
LC50 Inhalation - Rat	< 5 mg/l/4h	
Benzyl acetate (140-11-4)		
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)	

# Safety Data Sheet

Benzyl acetate (140-11-4)	
LD50 oral	2490 mg/kg
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)
benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg (Source: NLM_CIP)
LD50 oral	1570 mg/kg
Citrus medica limonum (Lemon) peel oil (800	08-56-8)
LD50 oral rat	2840 mg/kg (Source: NLM_CIP)
Citronellol Pure (106-22-9)	
LD50 oral rat	3450 mg/kg (Source: NLM_CIP)
LD50 oral	3450 mg/kg
LD50 dermal rabbit	2650 mg/kg (Source: EPA_HPV)
LD50 dermal	2650 mg/kg
Linalool (78-70-6)	
LD50 oral rat	2790 mg/kg (Source: NLM_CIP)
LD50 oral	2790 mg/kg
LD50 dermal rabbit	5610 mg/kg (Source: ECHA_API)
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	12.5 mg/l/4h
Dipropylene glycol monomethyl ether (34590	-94-8)
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
Skin corrosion/irritation : Additional information :	Not classified Based on available data, the classification criteria are not met
Serious eye damage/irritation :	Not classified
Additional information : Respiratory or skin sensitisation :	Based on available data, the classification criteria are not met  May cause an allergic skin reaction.
	Based on available data, the classification criteria are not met
Germ cell mutagenicity : Additional information :	Not classified Based on available data, the classification criteria are not met
Carcinogenicity :	Not classified
Additional information :	Based on available data, the classification criteria are not met
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable
Benzyl acetate (140-11-4)	
IARC group	3 - Not classifiable
Toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity : Additional information :	Not classified  Based on available data, the classification criteria are not met
·	,

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

STOT-single exposure : Not classified

Additional information :	Based on available data, the classification criteria are not met
Benzaldehyde (100-52-7)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure :	Not classified
Additional information :	Based on available data, the classification criteria are not met
Aspiration hazard :	Not classified
Additional information :	Based on available data, the classification criteria are not met

Toluene (108-88-3)	
Hydrocarbon	Yes

### 11.2. Information on other hazards

#### Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

# **SECTION 12: Ecological information**

Hazardous to the aquatic environment, long-term

## 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

: Toxic to aquatic life with long lasting effects.

(chronic)

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)	
LC50 - Fish [1]	0.452 mg/l Wolf, 1996d-27682
LC50 - Other aquatic organisms [1]	> 0.14 mg/l REACH DOSSIER Pimephales promelas
EC50 - Crustacea [2]	260 μg/l REACH Dossier
EC50 - Other aquatic organisms [1]	0.131 mg/l REACH Dossier
Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])
Ethyl maltol (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)
Aldehyde C-16 (77-83-8)	
LC50 - Fish [1]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: ECHA)
Carbitol (111-90-0)	
LC50 - Fish [1]	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	19100 – 23900 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through] Source: EPA)
EC50 - Crustacea [1]	3940 – 4670 mg/l (Exposure time: 48 h - Species: Daphnia magna)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Benzaldehyde (100-52-7)	Benzaldehyde (100-52-7)	
LC50 - Fish [1]	10.6 – 11.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: EPA)	
LC50 - Fish [2]	12.69 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: IUCLID)	
benzyl alcohol (100-51-6)		
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)	
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)	
Linalool (78-70-6)		
LC50 - Fish [1]	27.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: ECHA)	
EC50 - Crustacea [1]	20 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)	
Toluene (108-88-3)		
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)	
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)	
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])	
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)	
Dipropylene glycol monomethyl ether (34590-94-8)		
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)	

# 12.2. Persistence and degradability

DOUCE COUVERTURE		
Persistence and degradability	Not established.	
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl	-2-naphthalenyl)ethanone (54464-57-2)	
Persistence and degradability	Rapidly degradable	
Amyl cinnamic aldehyde (122-40-7)		
Persistence and degradability	Rapidly degradable	
ACETYL HEXAMETHYL TETRALIN (21145-77-	7)	
Persistence and degradability	Rapidly degradable	
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)		
Persistence and degradability	Rapidly degradable	
Vanillin (121-33-5)		
Persistence and degradability	Not established.	
Ethyl maltol (4940-11-8)		
Persistence and degradability	Rapidly degradable	

# Safety Data Sheet

Aldehyde C-16 (77-83-8)	
Persistence and degradability	Rapidly degradable
COUMARIN (91-64-5)	
Persistence and degradability	Rapidly degradable
Sandal Mysore Core (28219-60-5)	
Persistence and degradability	Rapidly degradable
Orange oil (8008-57-9)	
Persistence and degradability	Rapidly degradable
3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.)	: 2,2-dimethyl-3-(3-methylphenyl)propanol (103694-68-4)
Persistence and degradability	Rapidly degradable
Carbitol (111-90-0)	
Persistence and degradability	Rapidly degradable
Hydroxy (107-75-5)	
Persistence and degradability	Rapidly degradable
tetrahydro-2-isobutyl-4-methylpyran-4-ol, mix	ed isomers (cis and trans) (63500-71-0)
Persistence and degradability	Rapidly degradable
Benzaldehyde (100-52-7)	
Persistence and degradability	Rapidly degradable
Benzyl acetate (140-11-4)	
Persistence and degradability	Rapidly degradable
benzyl alcohol (100-51-6)	
Persistence and degradability	Rapidly degradable
Citrus medica limonum (Lemon) peel oil (800	8-56-8)
Persistence and degradability	Rapidly degradable
Citronellol Pure (106-22-9)	
Persistence and degradability	Rapidly degradable
CUPRESSUS FUNEBRIS WOOD OIL (85085-29	9-6)
Persistence and degradability	Rapidly degradable
Linalool (78-70-6)	
Persistence and degradability	Rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable
Dipropylene glycol monomethyl ether (34590-	94-8)
Persistence and degradability	Rapidly degradable

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

# 12.3. Bioaccumulative potential

DOUCE COUVERTURE	
Bioaccumulative potential	Not established.
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl	-2-naphthalenyl)ethanone (54464-57-2)
Partition coefficient n-octanol/water (Log Pow)	5.65 (at 30°C)
Amyl cinnamic aldehyde (122-40-7)	
Partition coefficient n-octanol/water (Log Pow)	2.498 (at 25 °C (at pH 6.2)
ACETYL HEXAMETHYL TETRALIN (21145-77-	7)
Partition coefficient n-octanol/water (Log Pow)	5.7 (at 24 °C)
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylind	deno[5,6-c]pyran; galaxolide; (HHCB) (1222-05-5)
BCF - Fish [1]	(1618 dimensionless (whole body w.w.)
Partition coefficient n-octanol/water (Log Pow)	5.3 (at 25 °C (at pH 7)
Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)
Bioaccumulative potential	Not established.
Ethyl maltol (4940-11-8)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 25 °C)
Aldehyde C-16 (77-83-8)	
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C (cis isomer)
COUMARIN (91-64-5)	
Partition coefficient n-octanol/water (Log Pow)	≥ 1.91 – ≤ 1.51 (at 25 °C (at pH 7)
Sandal Mysore Core (28219-60-5)	
Partition coefficient n-octanol/water (Log Pow)	3.8
Orange oil (8008-57-9)	
Partition coefficient n-octanol/water (Log Pow)	≥ 2.78 – ≤ 4.88
3-(2,2-dimethyl-3-hydroxypropyl)toluene; (alt.)	: 2,2-dimethyl-3-(3-methylphenyl)propanol (103694-68-4)
Partition coefficient n-octanol/water (Log Pow)	3.07 (at 20 °C)
Carbitol (111-90-0)	
Partition coefficient n-octanol/water (Log Pow)	-0.8
Hydroxy (107-75-5)	
Partition coefficient n-octanol/water (Log Pow)	1.68 (at 25 °C)
tetrahydro-2-isobutyl-4-methylpyran-4-ol, mix	ed isomers (cis and trans) (63500-71-0)
Partition coefficient n-octanol/water (Log Pow)	1.65 (at 23 °C (at pH >6.09-<6.74)
Benzaldehyde (100-52-7)	
BCF - Fish [1]	(no significant bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	1.4 (at 25 °C)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Benzyl acetate (140-11-4)		
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)	
benzyl alcohol (100-51-6)		
Partition coefficient n-octanol/water (Log Pow)	1.05	
Citronellol Pure (106-22-9)		
Partition coefficient n-octanol/water (Log Pow)	3.41 (at 25 °C)	
Linalool (78-70-6)		
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 20 °C (at pH 7)	
Toluene (108-88-3)		
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7)	
Dipropylene glycol monomethyl ether (34590-94-8)		
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)	

### 12.4. Mobility in soil

No additional information available

## 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

DOUCE COUVERTURE	
Other information	Avoid release to the environment.
Vanillin (121-33-5)	
Other information	Avoid release to the environment.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecological waste information

HP Code

- $: \ \, \text{Dispose of contents/container in accordance with licensed collector's sorting instructions}.$
- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP14 "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IMDG IATA ADN		RID
14.1. UN number or ID n	umber			
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shippin	g name			
ENVIRONMENTALLY HAZARDOUS	ENVIRONMENTALLY HAZARDOUS	Environmentally hazardous substance, liquid, n.o.s. (1-	ENVIRONMENTALLY HAZARDOUS	ENVIRONMENTALLY HAZARDOUS
SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8- Octahydro-2,3,8,8-	SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8- Octahydro-2,3,8,8-	(1,2,3,4,5,6,7,8-Octahydro- 2,3,8,8-tetramethyl-2- naphthalenyl)ethanone)	SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8- Octahydro-2,3,8,8-	SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8- Octahydro-2,3,8,8-
tetramethyl-2- naphthalenyl)ethanone)	tetramethyl-2- naphthalenyl)ethanone)	парпинаннут/ешанопе)	tetramethyl-2- naphthalenyl)ethanone)	tetramethyl-2- naphthalenyl)ethanone)
Transport document descr	iption			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8- Octahydro-2,3,8,8- tetramethyl-2- naphthalenyl)ethanone), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (1- (1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone), 9,	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8- Octahydro-2,3,8,8- tetramethyl-2- naphthalenyl)ethanone), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1-(1,2,3,4,5,6,7,8- Octahydro-2,3,8,8- tetramethyl-2- naphthalenyl)ethanone), 9
14.3. Transport hazard o	class(es)			
9	9	9	9	9
1	**************************************		**************************************	**************************************
14.4. Packing group				
III	III	III	III	III
14.5. Environmental haz	ards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes

## 14.6. Special precautions for user

#### **Overland transport**

Classification code (ADR) : Me

Special provisions (ADR) : 274, 335, 375, 601, 650

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13
and handling (ADR)

10/15/2025 (Revision date) EN (English) 29/35

# **DOUCE**\*\*COUVERTURE : 90

# Safety Data Sheet

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Orange plates : 90 3082

Tunnel restriction code (ADR) : EAC code : •3Z

Transport by sea

Special provisions (IMDG) : 274, 335, 375, 969

: 5 L Limited quantities (IMDG) : E1 Excepted quantities (IMDG) : LP01, P001 Packing instructions (IMDG) : PP1 Special packing provisions (IMDG) IBC packing instructions (IMDG) IBC03 Tank instructions (IMDG) T4 Tank special provisions (IMDG) TP1, TP29 Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

**Inland waterway transport** 

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601, 650

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601, 650

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading, unloading : CW13, CW31

and handling (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU-Regulations**

#### **REACH Annex XVII (Restriction List)**

Reference code	Applicable on	Entry title or description
3(a)	Orange oil ; Lemon oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	DOUCE COUVERTURE BEL128; 1- (1,2,3,4,5,6,7,8- Octahydro-2,3,8,8- tetramethyl-2- naphthalenyl)ethanone; Amyl cinnamic aldehyde; Aldehyde C-16; Sandal Mysore Core; Orange oil ; Majantol; Hydroxy; Florol; Benzaldehyde; Benzyl alcohol; Lemon oil ; Citronellol Pure; CUPRESSUS FUNEBRIS WOOD OIL; Linalool	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	DOUCE COUVERTURE BEL128; 1- (1,2,3,4,5,6,7,8- Octahydro-2,3,8,8- tetramethyl-2- naphthalenyl)ethanone; Amyl cinnamic aldehyde; Hexamethylindanopyran; Aldehyde C-16; Sandal Mysore Core; Orange oil; Majantol; Benzyl acetate; Lemon oil; CUPRESSUS FUNEBRIS WOOD OIL	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

#### VOC Directive (2004/42)

VOC content : 5.04950875 % (calculated value)(CARB VOC) (%w/w)

#### **Explosives Precursors Regulation (EU 2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (EC 273/2004)**

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

#### **National regulations**

#### **France**

Occupational diseases		
Code	Description	
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

#### Germany

VOC ordinance (ChemVOCFarbV) : VOC content : 5.04950875 % (calculated value)(CARB VOC)

(%w/w)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Major Accidents Ordinance (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

**Netherlands** 

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment
: Orange oil ,Lemon oil ,CUPRESSUS FUNEBRIS WOOD OIL are listed

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen : Orange oil ,Lemon oil ,CUPRESSUS FUNEBRIS WOOD OIL are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding

: None of the components are listed

SZW-lijst van reprotoxische stoffen –

None of the components are listed

Vruchtbaarheid

: None of the components are listed

SZW-lijst van reprotoxische stoffen - Ontwikkeling

: Toluene is listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

#### **Poland**

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).

Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).

The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).

Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).

Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).

Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).

The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)

Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended). Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).

ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as ammended)

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### **SECTION 16: Other information**

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H361	Suspected of damaging fertility or the unborn child.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.